

GNSS Receiver

T41

Laser Dual-camera RTK



T41 GNSS Receiver

T41 is a versatile GNSS receiver equipped with dual-laser cameras. It integrates a high-precision positioning module, IMU, AR, laser technology, and laser visualization to enable high-precision positioning, tilt measurement, AR real-world staking, and visualized laser point measurement. It boasts a maximum testing radius of up to 50 meters. The receiver features a robust magnesium-aluminum alloy design, offering durability and reliability. It supports hot-swappable batteries, allowing quick recharging without power interruption, thereby extending operational time.

CHARACTERISTIC

Full-System, Multi-Frequency GNSS Receiver

The receiver integrates a high-precision positioning module with 1,408 high-speed channels. It supports full-system and multi-frequency signal reception and processing, including: BDS: B1I, B2I, B3I, B1C, B2a, B2b, GPS: L1 C/A, L1C, L2C, L5, GLONASS: L1, L2, L3, Galileo: E1, E5a, E5b, E6, QZSS: L1, L2, L5, SBAS and NavIC systems.

Tilt Measurement

Equipped with an intelligent high-precision inertial navigation (IMU) module, the device offers real-time tilt compensation, eliminating the issue of "floating points" in RTK surveys.

AR Stake Out

A professional ultra-wide-angle camera provides HD real-world stake out capabilities. Its user-friendly AR stake out application ensures precise, one-shot staking performance.

Visualized Laser Measurement

Featuring a high-precision, millimeter-grade laser ranging module and a high-definition camera, the receiver enables precise point-and-measure functionality. The combination of high-accuracy inertial navigation and the camera's HD visuals ensures seamless operation even in complex environments.

Extended Battery Life

The receiver supports two detachable batteries that allow hot-swapping without power interruption. This enables quick battery replacement, significantly extending operational endurance.

T41 GNSS Receiver

Laser Dual-camera RTK



Main body magnesium alloy
ABS/PC top cover

1408 Channel
GPS GLONASS BDS GALILEO
QZSS SBAS IRNSS

Integrates precise laser ranging
with HD visualization

7.2V, 3400mAh*2
Over 20 Hours

Supports dual removable
powerful batteries for
extended operation

LASER MEASUREMENT



HEIGHT	DIAMETER	WEIGHT
103 mm	160 mm	850 g

≤2.5cm 3D error within 5m range
Enhanced with Green Laser.
Expands the range of measurable objects.

SPECIFICATION

SYSTEM

HARDWARE SYSTEM	ARM Cortex-A7 1.8GHz
OS	Linux

GNSS

GPS	L1C/A, L1C, L2P(Y), L2C, L5
GLONASS	L1, L2, L3
BDS	B1I, B2I, B3I, B1C, B2a, B2b(PPP)
GALILEO	E1, E5a, E5b, E6(PPP)
QZSS	L1, L2, L5
SBAS	L1(PPP)
NavIC (IRNSS)	L5*(Requires firmware support)

Channel	1436
Standard Output	NMEA-0183

Correction I/O Protocol	RTCM 3.X
-------------------------	----------

Frequency	20Hz max
-----------	----------

RTK Initialization Time	8 Sec
-------------------------	-------

Reacquisition Time	<1s
--------------------	-----

ACCURACY

SINGLE (RMS)	Horizontal: 1.5m / Vertical: 2.5m
--------------	-----------------------------------

DGPS (RMS)	Horizontal: 0.4m / Vertical: 0.8m
------------	-----------------------------------

RTK (RMS)	Horizontal: $\pm (8\text{mm}+1\text{ppm})$ Vertical: $\pm (15\text{mm}+1\text{ppm})$
-----------	---

Time Accuracy(RMS)	20ns
--------------------	------

High Accuracy Static	Horizontal: $\pm (2\text{mm}+1\text{ppm})$ Vertical: $\pm (4\text{mm}+1\text{ppm})$
----------------------	--

Static and Fast Static	Horizontal: $\pm (2.5\text{mm}+1\text{ppm})$ Vertical: $\pm (5\text{mm}+1\text{ppm})$
------------------------	--

Tilt Compensation ($\leq 60^\circ$)	<2cm
---------------------------------------	------

AR Stake Out Accuracy	Horizontal: $\pm (8\text{mm}+1\text{ppm})$ Vertical: $\pm (15\text{mm}+1\text{ppm})$
-----------------------	---

Laser Measurement	$\leq 2.5\text{cm}$ 3D error within 5m range
-------------------	---

SYSTEM PLATFORM

Bluetooth	BR+EDR+BLE
-----------	------------

WIFI	802.11 b/g/n
------	--------------

Network	LTE FDD: B1/2/3/4/5/7/8/12/13/ 18/19/20/25/26/28
	LTE TDD: B38/39/40/41
	WCDMA: B1/2/4/5/6/8/19
	GSM: B2/3/5/8

Storage	64GB storage
---------	--------------

Radio	Integrated high-power transceiver Frequency Range: 410~470MHz Power: 1W/2W/5W
-------	---

Radio	Protocols: TRIMTALK, TRIMMK3, SOUTH, TRANSEOT Air Baud Rate: 9600, 19200bps
-------	---

Laser Module	Type: Class 3R Range: 50m Precision: $\pm 5\text{mm} \pm 100 \times 10^{-6} \times D$, (D: Measurement Distance) Wavelength: 520 $\pm$ 20nm Power: 3.8mW
--------------	--

Laser Assist Camera	Sensor: 1/3.06 inch Resolution: 4224x3200 FOV: D44°H35°V26.5° Distortion: <1%
---------------------	--

AR Camera	AR Stakeout Supported Sensor: 1/2.8 inch Aperture: f/2.5 Resolution: 1920*1080 FOV: 70.3°H62.7°V38.6° Distortion: <0.38%
-----------	---

DISPLAY

LCD Panel	Sensor: 1.3 inch Resolution: 240*RGB*240
-----------	---

BATTERY / CHARGE

Capacity	7.2V, 3400mAh*2 (Removable, dedicated charger)
----------	---

Endurance	Over 20 hours(when applying controller network mode)
-----------	---

Charging	9~24VDC
----------	---------

ENVIRONMENT

Operating Temperature	-20°C~+60°C
-----------------------	-------------

Storage Temperature	-20°C~+70°C
---------------------	-------------

Shock Resistance	Can withstand a 1.5m drop at normal temperatures
------------------	---

Protection Rating	IP68
-------------------	------

PHYSICAL

Materials	Magnesium alloy casing with ABS/PC plastic top cover
-----------	---

Dimensions	$\Phi 160 \times 103\text{mm}$
------------	--------------------------------

Weight	850g(without battery)
--------	-----------------------

ACCESSORIES

T41	1 Unit
-----	--------

External Battery	2 PCS
------------------	-------

Battery Charging Cradle	2 PCS
-------------------------	-------

Radio Antenna	1 PCS
---------------	-------

🌐 www.toknavignss.com 📧 info@toknavignss.com

Manufacturers may update parameters at any time, please refer to the latest product information.



Europe, North & South America
Asia, Africa & Oceania
Tel & WhatsApp: +86 139 2607 5986 (Jeffrey)

Guangzhou Toksurvey Information Technology Co., Ltd
No. 9 Caipin Road, Building B, Room 801-6,
Huangpu District, Guangzhou, China