

🌐 www.toknavgnss.com

✉ info@toknavgnss.com

TOKNAV



GNSS Antennas

THA-7609A

Low-profile Drone Antenna

THA-7609A Helix Antenna

The THA-7609A Helix Antenna is a high performance GNSS antenna designed for high precision positioning service and offers superior satellite signal tracking, including GPS, GLONASS, GALILEO, BDS, as well as L-Band correction service. It could be used for applications as surveying and mapping, and various UAVs operations as aerial photography, remote sensing, infrastructure inspection, traffic control, and public security.

SPECIFICATION

SIGNAL TRACKING

GPS	L1/L2/L5
GLONASS	L1/L2
GALILEO	E1/E5a/E5b
BDS	B1/B2/B3
OZSS	L1/L2/L5/L6
SBAS	L1/L5
IRNSS	L5
L-Band	

LNA FEATURE

Nominal Impedance	50Ω
Polarization	RHCP
Axial Ratio	3dB
Gain RHCP (maximum)	1166-1278MHz 2.6dBi (@Zenith) 1559-1612MHz 2.8dBi (@Zenith) L-Band 1.5dBi (@Zenith)
Azimuth Coverage	360° (Omni-directional)
LNA Gain	33dB2dB
Noise Figure	2dB
Output/Input VSWR	2.0

Operation Voltage	+3.3V to +5V DC
Out of Band Rejection	Upper Band<1400MHz>30dB <1450MHz>33dB <1700MHz>30dB Lower Band<1000MHz>41dB <1100MHz>40dB <1130MHz>28dB
Operation Current	55mA
Group Delay Ripple	5ns

MECHANICAL

Dimensions	φ43.6*40.8mm
Connector	SMA-J
Weight	≤30.5g
Mounting	3-NO.3-48UNC screws fixed

ENVIRONMENTAL

Operating Temperature	-40 to +70
Storage Temperature	-55 to +70
Humidity	95% non-condensing
Protection	IP67

www.toknavgnss.com info@toknavgnss.com

Manufacturers may update parameters at any time, please refer to the latest product information.



Europe, North & South America
Asia, Africa & Oceania
Tel & WhatsApp: +86 139 2607 5986 (Jeffrey)

Guangzhou Toksurvey Information Technology Co., Ltd
No. 9 Caipin Road, Building B, Room 801-6,
Huangpu District, Guangzhou, China