



GNSS Antennas

TSA500

External Antenna with Six-constellation
and Eleven-frequency

TSA500 Survey GNSS Antenna

TSA500 is an external measurement antenna offers superior satellite signal tracking, including GPS, GLONASS, GALILEO, BDS, QZSS and SBAS signal reception. It meets the current requirements of multi-system compatibility for measurement devices. It finds extensive applications in geodetic surveying, marine measurement, channel surveying, land surveying, seismic monitoring, bridge deformation monitoring, landslide monitoring, container operations at ports, and other fields within the surveying industry.

SPECIFICATION

SIGNAL RECEIVED	
GPS	L1/L2
GLONASS	L1/L2
GALILEO	E1
BDS	B1/B2/B3
QZSS	L1/L2
SBAS	L1

ANTENNA FEATURE	
Nominal Impedance	50
Polarization	RHCP
Axial Ratio	3dB
Gain at Zenith (90°)	1205-1278MHz 5.5dBi(maximum) 1559-1615MHz 5.5dBi(maximum)
LNA Gain	40dB(typical)
Noise Figure	2dB

Output/Input VSWR	2.0
Operation Voltage	+3.3V to +12VDC
Operation Current	45mA(maximum)
Group Delay Ripple	5ns

MECHANICAL	
Dimensions	φ152mm*62.2mm
Connector	TNC female
Weight	500g
Mounting	BSW5/8"-11 screw, 12-14mm

ENVIRONMENTAL	
Temperature	Operating -40 to +85 Storage -55 to +85
Humidity	95% non-condensing
Protection	IP67
Regulatory Compliance	CE, FCC, RoHS

www.toknavgnss.com info@toknavgnss.com

Manufacturers may update parameters at any time, please refer to the latest product information.



Europe, North & South America
Asia, Africa & Oceania
Tel & WhatsApp: +86 139 2607 5986 (Jeffrey)

Guangzhou Toksurvey Information Technology Co., Ltd
No. 9 Caipin Road, Building B, Room 801-6,
Huangpu District, Guangzhou, China